Product data sheet Characteristics

GVAE11

Auxiliary contact block, TeSys Deca, 1NO +1NC, front mounting, for GV2





Main

Range	TeSys TeSys Deca	
Device short name	GVAE	·
Product or component type	Auxiliary contact block	
Product compatibility	GV2P GV2RT GV2ME GV3L GV2LE GV3P GV2L	
Mounting location	Front side	
Pole contact composition	1 NO + 1 NC	
Quantity per set	Set of 10	

Complementary

Complementary	
[Ui] rated insulation voltage	300 V conforming to UL 508 300 V conforming to CSA C22.2 No 14 250 V conforming to IEC 60947-1
[Ue] rated operational voltage	24240 V AC 2460 V DC
[lth] conventional free air thermal current	2.5 A
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A
Mechanical durability	100000 Cycles
Minimum switching current	5 MA
Minimum switching voltage	17 V
Rated operational power in VA	120 VA at 110120 V AC-15 - electrical durability: 100000 cycles 120 VA at 230240 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 60 VA at 48 V AC-15 - electrical durability: 100000 cycles
Rated operational power in W	15 W at 48 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 9 W at 60 V DC-13 - electrical durability: 100000 cycles
Tightening torque	1.4 N.M - on screw clamp terminals
Height	11 Mm
Width	45 Mm
Depth	29 Mm
Net weight	0.02 Kg

Environment

Environmental characteristic	Normal environment
Product certifications	UKCA

Packing Units

Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	17 G
Package 1 Height	1.2 Cm
Package 1 width	6 Cm
Package 1 Length	7 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	174 G
Package 2 Height	6.2 Cm
Package 2 width	12 Cm
Package 2 Length	7.4 Cm
Unit Type of Package 3	P06
Number of Units in Package 3	3520
Package 3 Weight	69.36 Kg
Package 3 Height	77 Cm
Package 3 width	80 Cm
Package 3 Length	60 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and-lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go-to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months

Product Life Status : Commercialised

